

PRESS NO.	Press Manufacture	Press Type	TONNAGE	MAX SHUT HT. (IN.)	MAX SHUT HT. (mm.)	Adjust down	STROKE (IN.)	STROKE (mm.)	FEEDHEIGHT	SPM	BED SIZE (FB X LR) IN.		BED SIZE (FB X LR) mm.		SLIDE HOLE PATTERN	WINDOW SIZE (IN.)	WINDOW SIZE (mm.)	FEEDER CAPACITY (WIDTH X STROKE)/ THICKNESS		
1	Verson	Straight Side	200	26	660.4		24	609.6	12+/- 3.0	10	72	x	108	1829	x	2743	6" Center T-slots	38	965.2	36 x 12/ 0.075"
4	Clearing	Straight Side	250	34	863.6		17	431.8	10 +/- 2.0	20-30	60	x	72	1524	x	1829	6" T-slots	43	1092.2	18 x 12/ 0.1875"
8	USI	OBI	200	20.5/ 16.5	520.7 / 419.1	5	10	254	8 +/- 3.0	32	35	x	54	889	x	1372	LR - 31" FB -23"	N/A		30 X 24/ 0.075"
9	Danly	OBI	110	14.5	368.3	3.5	6	152.4	9 +/- 3.0	40	27	x	42	685.8	x	1067	LR R - 10" LR F - 14" FB - 15"	N/A		
10	Verson	OBI	90	15	381		6	152.4	6	45	21	x	34	533.4	x	863.6	LR F - 16" FB - 7.25" CL	N/A		
11	Verson	OBI	90	12	304.8		6	152.4	6	45	21	x	34	533.4	x	863.6	LR F - 16" FB - 7.25" CL	N/A		
25	Nirgara	Straight Side	400	29	736.6	12	12	304.8	20 Max	30-60	54	x	96	1372	x	2438	6" T-slots	32	812.8	36 X .125 Servo
26	Nirgara	Straight Side	400	29	736.6	12	12	304.8	20 Max	30-60	54	x	96	1372	x	2438	6" T-slots	32	812.8	30 X .125 Servo
27	Blow	Straight Side	600	32	812.8	10	14	355.6	12-16"	20-40	60	x	144	1524	x	3658	6" T-slots	50	1270	48 x 60/
28	Blow	Straight Side	300	23	584.2	8	10	254	8"-14"	20-60	48	x	96	1219	x	2438	6" T-slots	32	812.8	30" X .125 Servo
29	Stamtec	Straight Side	300	27.5	698.5	7.5	9.75	247.65	N/A	30-60	55	x	98.5	1397	x	2502	6" T-slots	31.5	800.1	24 X 90/ 0.060"
34	Clearing	Straight Side	300	49.75	1263.65		10	254	20	20	54	x	108	1372	x	2743	6" T-slots	25	635	24 X 90/ 0.060"
35	Blow	Straight Side	1000	49	1244.6	10	20	508	22	15-30	84	x	192	2134	x	4877	6" T-slots	72	1828.8	72 x 24/ 0.021" TO 0.125"
36	Verson	Straight Side	500	55.5	1409.7	28	18	457.2	20	13-26	72	x	108	1829	x	2743	6" T-slots	51	1295.4	54 X 0.125 Max Thk.